

TOILET RECAULKING

Replacing the seal around the base of your toilets is a cost-effective means of improving the overall appearance of your bathroom and keeping the floors clean.



1 Remove all of the old caulk.



2 Vacuum the area to remove debris.



3 Clean and dry the area with Goof Off®.



4 Apply new caulk and smooth it.



PRO TIP

Be sure to caulk only the front and sides, leaving the back open to help you identify wax ring leaks.

SUPPLIES TO DO THE JOB



Warner Tool® 5-In-1 Glazier
Knife Tool
531430



Goof Off® Pro Strength
Remover
101110 ⚠ See Footnote



Maintenance Warehouse®
Microfiber Towel
111835



Stop Flow™ Caulk Gun With
Rotating Barrel
131411



DAP Kwik Seal Plus Kitchen
And Bath Caulk
108730 ⚠ See Footnote

⚠ WARNING: California Residents, this product contains chemical(s), which is/are known to the State of California to cause cancer and/or birth defects or other reproductive harm. Find more information by visiting hdsupplysolutions.com to review the specific product details.

© 2008 - 2022. HDS IP Holding, LLC. All Rights Reserved. HD Supply® and the HD Supply logo are trademarks of HDS IP Holding, LLC. For our terms and conditions, visit hdsupplysolutions.com/terms.

22-22431

3 EASY WAYS TO ORDER



MOBILE APP



1.800.431.3000



hdsupplysolutions.com