Special Orders Form — Exterior Slab & Prehung Doors

*All requests for custom items will be presented as a quote. Requests Jobsite Delivery Address: (20 doors or more) will not be placed directly on order without review and approval. *Must provide Jobsite form 100% filled out SHIP TO (Property Name) Date PO# Account # SHIPPING ADDRESS PHONE Purchaser Name Customer Phone # 7IP STATE Sales Rep Phone # Sales Rep Name ☐ Ship to warehouse: # *No jobsite form needed EMAIL ORDER CONFIRMATION TO EMAIL ADDRESS: Height: Width: Qtv: **Thickness** *Provide measurements from top of door 1/8 of an inch ☐ 1-3/4" (Exterior Std) **Prep Required?** □ No Material Handing/ ☐ Yes (MUST FULLY ☐ Steel (No Custom Size & Prep Swing COMPLETE BELOW) ☐ Fiberglass *Select One Below 1st Hinge Construction ☐ RHIS **Boring** Slab Peep Site Bore ☐ None Single Prehung ☐ Single Double Prehung ☐ 5.5" Double OUT ☐ Double + ½ bore Texas Only **Door Style** 2nd Bolt Half Bore ☐ Peep sight (1/2" dia.) 6 PANEL ☐ LHIS Exterior 2nd Hinge FI USH IN **FULL LITE MINIBLIND** Door **Bolt Bore** 1/2 LITE MINIBLIND OUT **FAN LITE** □ LHOS **Hinge Type** 10 LITE Lock IN ☐ Standard 9-LITE **OTHER** 3rd Hinge OUT ☐ Ball Bearing (Fiberglass Fire Rating STEEL ONLY □ None ☐ RHOS *Mill Sill & Satin Hinge Finish Prehung Only ☐ 20 minute IN Nickel Spring □ 90 minute ☐ Satin Nickel Hinges Only ☐ Brushed Chrome OUT 4th Hinge *Fire Rated doors can NOT be ☐ Antique Black *Required for field prepped or field altered. ☐ Brass doors over 8 *No customizations on Fire rated Hinge placement not required for pre-hung units unless requesting custom hinge prep doors. Do not fill in hinge or bore placements unless requesting custom locations. *All fire rated doors must come Not all options available in every market Custom widths of Entry doors not available. Custom heights are limited but available. Prehung. Slabs not available. Complete this section if pre-hung unit required: 90 min Fire Rated **Primed Jamb Size:** Sill Finish Other Jamb Material Size: Sill **Brickmold** ☐ Primed Wood Jamb size: *If sill required □ Textured Composite ☐ None ☐ None □ 4-9/16" □ 4.5-5.5" □ Mill Jambs for 20 Min Fire $\hfill\square$ Smooth Composite ☐ Brickmold ☐ Adjustable ☐ 5-1/4" ☐ Antique Black □ 5.5-6.5" Rated units available only in 4-9/16" and 6-9/16" ☐ Rot Resistant (ships loose) □ ADA □ 6-9/16" □ 6.5-7.5° □ 4-9/16" □ 7-1/4" Primed ADA sill only available in Mill finish. □ 7.5-8.5" □ 6-9/16" □ 8-9/16" ☐ Other (Please list size) DOOR ORDER TERMS Due to the custom requirements and lead times, door orders may not be cancelled and doors are not returnable. Additional charges may apply for changing sizes or quantities after the initial order is placed and will require a new worksheet. Delivery times may vary, and freight charges may apply. If ordered, you must inspect product for damages upon receipt. Any damage must be noted when signing for delivery so credit can be issued. By signing below you agree to the terms stated above and that all measurements shown above are correct.